




ZANGAN DISTRIBUTION
TRANSFORMER CO.(P.J.S.C)



شرکت ترانسفورماتور توزیع زنگان
سهامی عام

Three - Phase Cast Resin Transformer For Indoor Installation


Standard	IEC60076-11	Serial No.	
Type	TGUN6344	Year	
Kind	Power Trans.	Conductor Mat. HV/LV	Al/Al
Rated Power	2000 kVA	Cooling Method	AN
Vector Group	Dyn5	Fan's Apparent Power	- W/V
Impedance Voltage	%	Altitude Above Sea	1000 m
Max. Temperature Rise	100 K	Protection Degree	IP00
Frequency	50 Hz	Transformer Weight	5010 kg
HV Insulation Level	24/50/95 kV		
LV Insulation Level	1.1/3/- kV		
Thermal Class HV/LV	F/F		

HV Side				LV Side	
Pos.	Tap Changer Connection	Voltage(V)	Connection	Voltage(V)	Connection
1	5-6	21000		400	
2	7-5	20500			
3	4-7	20000			
4	8-4	19500			
5	3-8	19000			
Rated Current		57.74 A	2886.75 A		
Environmental/Climatic/Fire Behavior Classes: E2/C2/F1					

Iran Transfo After Sales Services Co.
www.itass.ir Email: itass@iran-transfo.com
MADE IN IRAN-ZANJAN

شرکت خدمات پس از فروش ایران ترانسفو
Fax: 024-32221353 Tel: 024-32221346-52
ساخت ایران - زنجان

4 holes on the corners $\varnothing = 3.5\text{mm}$
 Distance between of holes = 136x136 mm
 Uncertain tolerances according to DIN ISO 2768-m

Index	Mod.No.	Date	Modifications	Signature	Title:
					Name Plate 2000 kVA
					Ordered by:
Tolerance:		Group:	Applied by:	Drawing Identification:	
Scale: --			Monfared	I T R I - - R 1 1	
			Check by:	Drawing No.:	
			Karamzadeh	N D 0 U 0 6 - 0 0 5 -	
 شرکت ترانسفورماتور توزیع زنگان ZANGAN DISTRIBUTION TRANSFORMER CO.		Approved by:	Date:	Page.Count No.:	Page No.:
		Joulaei	1401/02/20		11 of 13